

MultiPro Multi-Gas Detectors



Features

Design

- Compact & Rugged
- One button operation
- Easy to read front mounted backlit display
- Over-molded boot

Optional Slip-on Pump

- Software controlled pump
- Powered by the *MultiPro* battery
- Automatic low flow alarm
- Automatic leak test before every use

Recording

- Automatic event logger (20 events, including sensor type, max, average, time and duration)
- Black-Box recorder with over 40 hours of storage
- Available with datalogging for convenient and easy downloading to a computer

Sensors and Calibration

- Three sensors. O₂, LEL and up to two toxic channels using Biosystems' Duo-Tox two channel CO/H₂S sensor
- Field replaceable sensors
- One button auto calibration
- Calibration due reminder
- Sensor span reserve indicators during calibration for predictive maintenance

Batteries

- Alkaline or rechargeable (Li-Ion) versions
- Up to 22 hours of run time
- Drop-in fast charger
- Recharges in less than 5 hours

Standard Accessories

- Operators guide
- Training CD-ROM
- Rechargeable Li-Ion version includes charger
- Clothes Clip
- Laminated quick reference guide
- Calibration adapter

Certifications

- ATEX II 2 G Ex d ia IIC T4 *
- UL Class I, Division 1, Groups A, B, C, D Temp. Code T4
- CSA Class I, Division 1, Groups A, B, C, D Temp. Code T4
- IECEx Ex d ia IIC T4 *
- CQST (China) Ex ia IIC T4