

LIGHT METER *4 light type*

Model : LX-1108

ISO-9001, CE, IEC1010



FEATURES

- * 5 ranges :
40.00/400.0/4,000/40,000/400,000 Lux.
- * Resolution :
0.01 Lux to 100 Lux.
0.01 Ft-cd to 10 Ft-cd.
- * Selection of lighting type (Tungsten, Fluorescent, Sodium or Mercury).
- * Sensor used the exclusive photo diode & color correction filter, spectrum meet C.I.E. photopic.
- * Sensor cosine correction factor meet standard.
- * Separate Light Sensor allows user to measure the light at an optimum position.
- * Lux & Foot-candle unit selection.
- * Large LCD display with bar graph.
- * Water resistance front panel
- * Zero adjusting button.
- * Data hold and Peak hold.
- * Memory function with Recall. Auto
- * Auto power off or manual power off.
- * RS-232 computer data output.

Lutron

LUTRON ELECTRONIC

The Art of Measurement

4 light type selection

LIGHT METER

Model : LX-1108

FEATURES	
* 5 ranges : 40.00/400.0/4,000/40,000/400,000 Lux, wide measuring range.	* Large LCD display with bargraph and indicator.
* High resolution : 0.01 Lux to 100 Lux, 0.01 Fc to 10 Fc	* Water resistance front panel
* Selection of lighting type (Tungsten, Fluorescent, Sodium or Mercury).	* Use the rubber key for the function select.
* Sensor used the exclusive photo diode & color correction filter, spectrum meet C.I.E. photopic.	* LSI circuit provides high reliability and durability.
* Sensor cosine correction factor meet standard.	* Zero adjusting button.
* Separate Light Sensor allows user to measure the light at an optimum position.	* Data hold to freeze the desired reading.
* Lux & Foot-candle unit selection.	* Peak hold measurement.
	* Memory function to display the max. & min. display value with Recall.
	* Auto power auto off or manual power off.
	* Compact size and excellent operation.
	* Built-in low battery indicator.
	* RS-232 computer serial data output.

GENERAL SPECIFICATIONS			
Display	Large LCD display. LCD size 52 x 38 mm, 5 digits. with bargraph indicator.	Data Output	RS-232 serial data output.
Measurement & ranges	5 ranges : 40.00/400.0 Lux. 4,000/40,000/400,000 Lux.	Operating Temperature	0 to 50 °C (32 to 122 °F).
Unit	Lux, Foot-candle (Ft-cd).	Operating Humidity	Max. 80% RH.
Lighting Type Selection	Tungsten, Fluorescent, Sodium, Mercury lamp.	Power Supply	DC 9V battery. 006P, MN1604 (PP3) or equivalent.
Sensor	The exclusive photo diode & color correction filter, spectrum meet C.I.E. Cosine correction factor meet standard.	Power Consumption	Approx. DC 8 mA.
Zero Adj.	External adjustment by pushing button. (40.00 Lux range only)	Weight	220 g/0.48 LB.
Peak Hold	To hold the peak display.	Dimension	<i>Main instrument :</i> 200 x 68 x 30 mm (7.9 x 2.7 x 1.2 inch). <i>Sensor probe :</i> 82 x 55 x 7 mm (3.2 x 2.2 x 0.3 inch).
Data Hold	To freeze the display value.	Accessories Included	Instruction Manual... 1 PC. Light Sensor with protection cover..... 1 PC.
Memory	Save the max. & min. value with Recall.	Optional Accessories	RS232 cable, UPCB-02 Application Software, SW-U801-WIN Hard carryingt case, CA--06 Soft carryingt case, CA--05A
Power Off	Auto or manual power off.		
Over and Under range Indication	Over range Indicator : " - - - - " Under range Indicator : " _ _ _ _ "		

ELECTRICAL SPECIFICATIONS (23 ± 5 °C)				
Measurement	Range	In-range Display	Resolution	Accuracy
Lux	40.00 Lux	0 - 40.00 Lux	0.01 Lux	± (3% rdg + 0.5 % F.S.)
	400.0 Lux	36.0 - 400.0 Lux	0.1 Lux	
	4,000 Lux	360 - 4,000 Lux	1 Lux	
	40,000 Lux	3,600 - 40,000 Lux	10 Lux	
	400,000 Lux	10,000 - 400,000 Lux	100 Lux	< 100,000 Lux : ± (3% rdg + 0.5 % F.S.) ≥ 100,000 Lux : @ for reference only
Foot-candle (Fc)	4.000 Fc	0 - 3.720 Fc	0.001 Fc	± (3% rdg + 0.5 % F.S.)
	40.00 Fc	3.35 - 37.20 Fc	0.01 Fc	
	400.0 Fc	33.5 - 372.0 Fc	0.1 Fc	
	4,000 Fc	335 - 3,720 Fc	1 Fc	
	40,000 Fc	930 - 37,200 Fc	10 Fc	< 9,300 Fc : ± (3% rdg + 0.5 % F.S.) ≥ 9,300 Fc @ for reference only

Note : Accuracy tested by a standard parallel light tungsten lamp of 2856 K degree temperature.

* Appearance and specifications listed in this brochure are subject to change without notice.

CAT-0403-LX1108